

APPLICATION
FOR
UNITED STATES LETTERS PATENT

TITLE: OPTICAL TO MAGNETIC ALIGNMENT IN MAGNETIC
TAPE SYSTEM

APPLICANTS: George Bellesis, Leo Guglielmo, Tzuochang
Lee, Robert Johnson and James Fitzpatrick

Kenneth F. Kozik
Fish & Richardson P.C.
225 Franklin Street
Boston, MA 02110-2804
Tel.: (617) 542-5070
Fax: (617) 542-8906

CERTIFICATE OF MAILING BY EXPRESS MAIL

Express Mail Label No. EL 298 426 011 US

I hereby certify under 37 CFR §1.10 that this correspondence is being deposited with the United States Postal Service as Express Mail Post Office to Addressee with sufficient postage on the date indicated below and is addressed to the Commissioner for Patents, Washington, D.C. 20231.

Date of Deposit August 20, 2001

Signature Samantha Bell

Typed or Printed Name of Person Signing
Certificate Samantha Bell

TECHNICAL FIELD

BACKGROUND

Head positioning optical servo systems are employed to position a read and/or write head in a magnetic tape system over a selected track of data; these systems are generally referred to as laser-guided magnetic recording (LGMR) systems. Misalignment between the read/write head and the data track

may cause data errors during read back and data loss on adjacent tracks during writing.

To ensure a working head positioning optical servo system (including read while write) and also magnetic tape cartridge
5 interchange capability the optical servo system should be aligned with the magnetic read/write head during its manufacture and prior to shipment to an end-user.

SUMMARY

In a general aspect, the invention features a method of
10 positioning a selected recording channel on a recording head relative to an optical servo system in a read/write assembly including positioning the optical servo system at a first position relative to the selected recording channel in the read/write assembly, processing an alignment tape in the
15 read/write assembly to determine a lateral offset between the optical servo system and the selected recording channel, and positioning the optical servo system at a second position relative to the selected recording channel using the lateral offset.

20 In a preferred embodiment, the alignment tape includes a track of longitudinal equally spaced apart alignment voids. Processing includes writing a track of data to the alignment tape over the track of alignment voids, imaging a section of

15 Alternatively, processing includes writing and
subsequently reading a track of data to a front major surface
of the alignment tape on the track of alignment voids with a
write head and a read head of the selected recording channel,
monitoring a bit-error ratio (BER) from reading the track of
20 data, and correlating the bit-error ratio (BER) to the lateral
offset. Correlating includes relating a maximum BER to the
lateral offset. A negative lateral offset value indicates the
optical servo system is laterally above the selected recording
channel and a positive lateral offset indicates the optical

Alternatively, processing includes providing a plurality of longitudinally arranged equally spaced apart alignment void tracks on the alignment tape, moving the recording head across the tracks in a motion perpendicular to a motion of the alignment tape, writing and reading a magnetic signal to the alignment tape by the selected recording channel at a higher frequency than the frequency of alignment voids moving past the selected recording channel to determine an amplitude demodulated magnetic signal, directing a beam of light by the optical servo system to the alignment tape to determine an optical signal, and determining a timing difference between the envelope of the demodulated magnetic signal and the envelope of the optical signal. Determining may include the timing difference between a peak in the envelope of the demodulated magnetic signal and a peak in the envelope of the optical signal. Determining may include calibrating the timing difference using the velocity measured from the timing difference between peaks in the envelope of the optical signal. Determining may include the cross-correlation function to find the timing difference between the envelope of the demodulated magnetic signal and the envelope of the

optical signal. The velocity is determined from the separation of peaks in the cross-correlation function. The lateral offset is set equal to the timing difference divided by the velocity.

- 5 Alternatively, processing includes providing a plurality of longitudinally arranged equally spaced apart alignment void tracks on the alignment tape, moving the recording head across the tracks in a motion perpendicular to a motion of the alignment tape, directing multiple beams of light by the
- 10 optical servo system to the alignment tape to determine a number of optical signals, and determining a timing difference between the envelope of one optical signal and the envelope of another optical signal. The optics are rotated to bring the timing difference divided by the velocity to a desired value.
- 15 Determining may include the cross-correlation function to find the timing difference between the envelope of one optical signal and the envelope of another optical signal.

- 20 The alignment tape includes longitudinal tracks on a second major surface of the tape, and recording channel positioning alignment voids. Processing includes suspending the alignment tape in a coupon, positioning the alignment tape with the coupon over a recording channel pair to position a line from one element of a channel pair to another, and positioning the optical servo system such that one generated

optical spot is centered on a middle one of the longitudinal tracks and other generated optical spots are offset by a desired amount. Passing the tape through a laser system generates the tracks. Positioning includes viewing the
5 alignment tape under a microscope, and adjusting the alignment tape's position with a precision translation and rotation stage attached to the coupon.

In another aspect, the invention features an alignment tape for positioning a selected recording channel of a
10 recording head relative to an optical servo system in a read/write assembly including an elongated continuous web of flexible plastic substrate material having two edges and defining a front major surface and a back major surface, a magnetic storage medium formed on the front major surface, an
15 inert medium formed on the back major surface, and a track of alignment voids for indicating actual lateral displacement of the selected recording channel relative to the optical servo system.

In a preferred embodiment, the track of alignment voids
20 is formed by ablation by a pulsating laser beam of sufficient power to penetrate the back major surface through to the front major surface leaving visible the flexible plastic substrate of the alignment tape.

In a preferred embodiment, the method further includes aligning a data track with the selected recording channel using optical servo system and the stored lateral offset during tape travel across the selected recording channel.

15 A check of optical alignment both before and after tape
drive assembly may be implemented and can be made without
disassembly of a completed tape drive. Optical alignment is
done rapidly in a manufacturing environment and insures tape
interchange between diverse tape drive assemblies by closely
20 aligning the optical servo system to a recording channel, and
by providing a measure of residual misalignment, enabling
compensation techniques to be implemented.

7

below. Other features, objects, and advantages of the invention will be apparent from the description and drawings, and from the claims.

DESCRIPTION OF DRAWINGS

5 FIG. 1 is a block diagram of an exemplary magnetic tape
recording system.

FIG. 2 is a schematic diagram of a cross section of the read/write assembly of FIG. 1.

FIG. 3 is a schematic diagram of an exemplary alignment
10 tape.

FIG. 4 is a block diagram of an exemplary optical servo writer system.

FIG. 5 is a block diagram of an exemplary microscope.

FIG. 6A is an illustration of a first exemplary image of
15 the alignment tape under a microscope.

FIG. 6B is an illustration of a second exemplary image of the alignment tape under a microscope.

FIG. 7 is an exemplary graph of track offset verses bit-error ratio (BER).

20 FIG. 8 is a schematic diagram of a second exemplary
alignment tape.

FIG. 9 is an exemplary graph of optical and magnetic signal envelopes.

FIG. 10 is an illustration of an alignment tape used in conjunction with a positioning coupon.

Like reference symbols in the various drawings indicate like elements.

5

DETAILED DESCRIPTION

Referring to FIG. 1, an exemplary magnetic tape recording system 10 includes a delivery system 12, a read/write assembly 14 and a pickup system 16. The delivery system 12 houses a magnetic tape 18. The magnetic tape 18 travels past a recording head 20 and an optical servo system 22 contained in the read/write assembly 14 and is delivered to the reel pickup system 16. The recording head 20 reads and writes information, generally referred to as data, onto one or more data tracks on the magnetic tape 18 as it travels from the delivery system 12 to the pickup system 16. As the magnetic tape 18 passes over the recording head 20 the magnetic tape 18 may become misaligned with respect to the intended track position due to, for example, lateral tape motion (LTM). Changes in lateral tape position can be detected by the optical servo system 22 in conjunction with optical servo tracks located on the tape 18 and compensated for via a closed servo control loop, described below.

Referring to FIG. 2, the read/write assembly 14 includes the recording head 20 and the optical servo system 22. An actuator 24 is shown connected to the read/write assembly 14. In operation, the magnetic tape 18 moves across the recording head 20 and a set of data tracks (not shown) are written or read from the tape 18. In one example, the read/write assembly 14 includes a series of recording channels 26, 28, 30 and 32 residing on the recording head 20, thus writing four tracks simultaneously on the tape 18. Four read heads about 0.1 inches downstream (not shown) immediately read and verify the data just written. The optical servo system 22 utilizes one or more optical servo tracks on a second major surface 34 of the magnetic tape 18 to detect lateral tape motion (LTM) of the magnetic tape 18 along an axis 36. Compensation of LTM is done by positioning the read/write assembly 14 relative to the tape 18 via movement of the actuator 24. Specifically, the optical servo system 22 directs a beam of light upon a particular one of the optical servo tracks located on the second major surface 34 of the tape 18. Reflections of the beam of light from the optical servo track result in electronically discernible LTM position error signals. The resultant position error signals are sent to an optical feedback control loop that generates a bi-directional head position correction sending current to a coil motor that

results in a servo bias torque. The bias torque is applied to the actuator 24 to pivot the read/write assembly 14 along the axis 36 relative to the tape 18 and thereby follow the tape 18 despite the presence of LTM.

5 As indicated above, LTM is an undesirable motion of the tape 18 in a lateral direction along the axis 36 that is transverse to the tape direction. LTM may be caused by many factors including tape slitting variations, tension variations, imperfections in the guiding mechanism, friction
10 variations in the recording head 20, and environmental factors such as heat and humidity. These factors affect LTM in various ways. Some cause abrupt momentary jumps along the axis 36 while others may cause a slower variation of tape position along the axis 36. Generally, LTM is unpredictable
15 and unrepeatable and is compensated for by using the optical servo system 22.

During manufacture of the read/write assembly 14, the optical servo system 22 is aligned to one of the recording channels 26, 28, 30, 32, recording channel 30 for example,
20 using a special alignment tape. The alignment tape provides an offset between the optical servo system 22 and the recording channel 30 that is used to align or position the two before the read/write assembly 14 is shipped to customers. During the manufacture of the read/write assembly 14, the

5

10

15

20

Referring to FIG. 3, an alignment tape 50 includes a track of special marks referred as alignment voids 52. The term void as used herein refers to a location of the alignment tape 50 in which the magnetic material on a first major surface of the alignment tape 50 is absent and in which the generally inert backing material on a second, opposite, major surface of the alignment tape 50 is absent, leaving only an area of exposed base film. Specifically the alignment voids 52 are a series of longitudinally arranged, equally spaced,

spots of exposed base film. In operation, the track of alignment voids 52 is utilized during manufacturing of the read/write assembly 14 to align, as mentioned above, the optical servo system 22 with one of the recording channels 26, 28, 30 or 32.

Referring to FIG. 4, an exemplary laser system 60 for producing a track of alignment voids 52 includes a laser source 62, a servo writer optics system 64 and a lens 66. The laser source 62 generates a beam of collimated light 68. In a preferred embodiment, the light 68 is in the ultraviolet (UV) range of the spectrum. The collimated light 68 enters the optics system 64 where it generates a focused beam 70. The focused beam 70 is passed through the lens 66 and directed on to the alignment tape 50. Upon hitting the alignment tape 50, the focused beam 70 removes pieces of inert backing material from the second major surface of the alignment tape 50 and magnetic material from the first major surface of the alignment tape 50, leaving a track of alignment voids 52. In operation, the laser source 62 is pulsed at such a frequency to result in generating a longitudinally arranged equally spaced apart track of alignment voids 52. More specifically, a combination of high power and short wavelength, for example, 31 milliwatts with a wavelength of 355 nanometers, of the focused beam 70 penetrates both the first major surface and

the second major surface of the alignment tape 50. A polyethylene terephthalate (PET) base film of the alignment tape 50 is transparent to UV light 68 of the laser source 62. Thus, the focused beam 70 penetrates into the first major surface and the second, opposite, major surface of the alignment tape 50, leaving only the base film of the alignment tape 50 where the focused beam 70 hits. By adjustment of the height of the drive moving the alignment tape 50 relative to the height of the laser source 62 and optics 64 and 66, the track of alignment voids 52 is positioned on the alignment tape 50 at a distance along axis 36 that can match standard optical servo tracks. This ensures that the actuator 24 is able to move the optical servo system 22 into position to see the track of alignment voids 52.

There are many ways to use the alignment tape 50 to perform alignment of a selected recording channel with the optical servo system 22 as part of the manufacturing process and prior to shipment of the fully assembled magnetic tape recording system 10 to an end-user.

In one operation, a selected recording channel is blindly aligned to the optical servo system 22 and manually set in place using the adapter 38. This initial alignment is blind since there is no practical way to visually align a selected recording channel to the optical servo system 22 with any high

degree of accuracy. Only through extremely tedious methods of trial and error might the selected recorded be visually aligned to the optical servo system 22. The alignment tape 50 is placed in the magnetic tape recoding system 10. The selected recording channel writes a single linear track of data while the optics detect the track of alignment voids 52. After the single track of data is written the alignment tape 50 is removed from the magnetic tape recording system 10 and a section of the alignment tape 50 viewed under a microscope, such as exemplary microscope 75 in FIG. 5. Imaging of the section of alignment tape 50 is used in conjunction with the microscope 75. Example imaging techniques are magnetic force microscopy and optical microscopy using ferrofluids.

Referring to FIG. 6A, a first exemplary image 100 of the alignment tape 50 after the track of data has been written illustrates a single track of data 80 and the track of alignment voids 52, as viewed under the microscope 75. A center 82 of the track of data 80 is not centered relative to a center 84 of the track of alignment voids 52. A distance 86 between the center 82 of track of data 80 and the center 84 of the track of alignment voids 52 represents an actual lateral offset 86 between the selected recording channel and the optical servo system 22 measured in, for example, micrometers. Recall that before the alignment tape 50 is placed in the

magnetic tape recording system 10, the selected recording channel and the optical servo system 22 are blindly aligned and positioned relative to each other by using the adjuster 38. The actual lateral offset 86 can be stored for use during system 10 operation or to finely adjust the position of the selected recording channel and the optical servo system 22 by further manual adjustment using the adjuster 38. The optical servo system 22 can be locked in place relative to the selected recording channel for further processing of the read/write assembly 14 during its manufacture.

By way of another example, referring to FIG. 6B, a second exemplary image 102 of the alignment tape 50 after the selected recording channel has written the track of data 88 shows a single track of data 88 and the track of alignment voids 52. A center 90 of the track of alignment voids 52 is also the center of the track of data 88. Thus, the actual lateral offset is zero and may be stored for use during system 10 operation. This means that the selected recording channel and the optical servo system 22 are aligned and no further adjustment is needed. The read/write assembly 14 is ready for further processing during its manufacture.

In another example, an actual lateral offset is determined using the alignment tape 50 and a read-after-write process. Here again, initially, the selected recording

total number of bits transmitted, received, or processed over some stipulated period. Examples of bit error ratios are (a) transmission Bit-Error-Ratio, i.e., the number of erroneous bits received divided by the total number of bits transmitted; 5 and (b) information Bit-Error-Ratio, i.e., the number of erroneous decoded (corrected) bits divided by the total number of decoded (corrected) bits. The BER is usually expressed as a coefficient and a power of 10. A BER of the selected recording channel that is lined up (or nearly lined up) with 10 the optical servo system 22 greatly increases whenever data is written and read directly over the track of alignment voids 52 because data cannot be written where magnetic material on the alignment tape 50 is missing. The BER decreases when the selected recording channel is not on the track of alignment 15 voids 52 because data can be written where the magnetic material on the alignment tape 50 is present.

Referring to FIG. 7, an exemplary graph 110 of the BER 114 by the selected recording channel versus track offset 112 across two tracks of the alignment tape 50 is illustrated. 20 Here again, prior to the run, the selected recording channel is blindly aligned to the optical servo system 22 and set in place at a first position using the adjuster 38. The selected recording channel writes a single track of data to the track of alignment voids 52 as the head moves across two tracks of

alignment voids. The optics 22 detects the movement across the two tracks. A first peak 116 represents a following of the BER of reads-after-writes by the selected recording channel across the first track, while a second plot 118

5 represents a following of the BER of reads-after-writes by the selected recording channel across the second track. The known separation of alignment void tracks allows a calibration to be made of the offset distance 112.

FOI b1 b7C b7D
10 In the first track 116, the plot goes through a maximum BER at point 120 and correlates to a track offset of 0 by the selected recording channel. This indicates the selected recording channel is lined up directly on the track of alignment voids 52, and thus aligned properly with the optical servo system 22. For the second track by the selected
15 recording channel, the plot 118 goes through a maximum BER at point 122. Point 122 correlates to a linear track offset of 24 μm , the separation between tracks on the alignment tape. This can be used to calibrate an offset for those cases when the peak 120 is at a non-zero offset. Thus, if in a separate
20 and unique run of the BER 114 versus track offset 112, the peak 120 occurs at an offset of count 500 and the peak 122 occurs at an offset count of 1500, then that means that the alignment of the selected recording channel and the optical servo system 22 is off by approximately half of 24, or 12 μm

and the optical servo system 22 needs to be adjusted 12 μm laterally by the adjuster 38. Correlation of the maximum BER to a positive lateral offset means the optical servo system 22 has to be moved laterally up relative to the selected

5 recording channel, while correlation of the maximum BER to a negative lateral offset means the optical servo system 22 has to be moved laterally down relative to the selected recording channel. In each case, the adjuster 38 is used to laterally position the optical servo system 22 an amount equal to the
10 lateral offset. Once the optical servo system 22 is adjusted relative to the selected recording channel into a second position using the determined lateral offset, and the read/write assembly 14 is ready for further processing during its manufacture.

15 In another example, a scanning head method is utilized in conjunction with the alignment tape 52 and the optical servo system 22 to determine an offset between the selected recording channel and the optical servo system 22. Referring to FIG. 8, the laser system 60 for producing tracks of
20 alignment voids (of FIG. 4) is used to generate multiple parallel longitudinal tracks of alignment voids 90 on the alignment tape 50. This is accomplished by having the laser source 62 direct multiple beams of light to the servo optics system 64 and focusing the multiple beams onto the alignment

5 In operation, the selected recording channel is moved slowly across the multiple tracks of alignment voids 90 in a motion perpendicular to the alignment tape 50. During the perpendicular motion the selected recording channel writes and reads a single frequency magnetic signal on the first major surface of the alignment tape 50. The amplitude of the magnetic signal detected by the read head on the selected recording channel decreases whenever an alignment void passes across the read head, then the magnetic signal is amplitude modulated. The optical servo system 22 is turned on and an optical spot directed by a laser source in the optical servo system 22 towards and reflected off of the second, opposite, major surface of the alignment tape 50 where an optical signal is detected by an optical sensor in the optical servo system 22. The demodulated magnetic signal and the optical signal have the same frequencies, corresponding to the rate at which alignment voids, traveling with the alignment tape, move past the recording head 20 and the optical servo system 22. The selected recording channel and the optical servo system 22 are aligned when the envelope of the demodulated magnetic signal

Referring to FIG. 9, an exemplary graph 130 tracking the envelope of the demodulated magnetic signal 132 and the envelope of the optical signal 134 is illustrated. When the selected recording channel is centered over an alignment void in any one of the tracks of alignment voids 90 the envelope of the demodulated magnetic signal peaks at point 136, for example, since the amplitude modulation of the magnetic signal at this point is a maximum. When a spot of light generated by the optical servo system 22 is centered over an alignment void, the light reflected is a minimum, and thus the current photo detector in the optical system 22 is a minimum. However, typically an amplifier generates a voltage signal that peaks when the current is a minimum, thus when a spot of light generated by the optical servo system 22 is centered over the same alignment void in the multiple tracks of alignment voids 90 the envelope of the optical voltage signal peaks at point 138. Knowing the track pitch of the alignment voids 90, which can be controlled by adjustment of the servo writer optics 64 and can be measured by the microscope 75, one knows that each peak in the envelope of the optical signal 134 corresponds to the track pitch. Similarly, the separation of

voids 90. Equally spaced peaks indicate a constant velocity of the head assembly. Then the timing difference t is the difference in time between peaks 136 and 138 and is converted to micrometers by multiplying by the velocity.

24

5 The metal coupon 158 is also sized to fit between the recording channels of the recording head 20 and the optical servo system 22 and includes precision translation and rotation stages 160 to manually position the coupon 158, and consequently the alignment tape 150, accurately within the read/write assembly 14. In addition, a microscope, such as
10 the microscope 75 of FIG. 5, is mounted to the read/write assembly 14 to aid in viewing the position of the alignment tape 150 relative to the recording channels and the optical servo system 22.

25

The adjuster 38 is moved by a precision translation stage 160 to position the optical spot over a center of a middle one of the multiple continuous longitudinal arranged tracks 152. Once centered, the position is fixed as a final position. The
5 read/write assembly 14 is ready for further processing in its manufacture.

A number of embodiments of the invention have been described. Nevertheless, it will be understood that various modifications may be made without departing from the spirit
10 and scope of the invention. Accordingly, other embodiments are within the scope of the following claims.

WHAT IS CLAIMED IS: